

	AP-400	AP-500	AP-600	AP-725	AP-850
WATER					
GALLON CAPACITY (BOILER)	13.0	12.0	12	17.0	16
HEATING SURFACE (SQ. FT.) (BOILER)	55.3	73.0	73.02	84.6	99.88
DRAIN	1" NPT	1" NPT	1" NPT	1"NPT	1" NPT
20°F ΔT WATER FLOW (GPM)	39	49	59	71	83
HEAD LOSS (FT. OF HD.)	3.5	4.8	4.4	4.9	5.7
40°F ΔT WATER FLOW (GPM)	20	24	29	35	41
HEAD LOSS (FT. OF HD.)	3	3	2.8	3	3.3
MAX. WORKING PRESSURE (PSI)	160	160	160	160	160
# OF RELIEF VALVES	1	1	1	1	1
RELIEF VALVE SIZE	3/4"	3/4"	3/4"	3/4"	3/4"
RELIEF VALVE RATING (MBH)	697,000	697,000	697,000	1,352,000	1,352,000
RELIEF VALVE PRESSURE RATING (PSI)	50	50	50	50	50
GAS					
INLET CONNECTION	1"	1"	1"	1"	1"
MAX. INLET PRESSURE, NAT	14"	14"	14"	14"	14"
MIN. INLET PRESSURE, NAT	4"	5"	4"	4"	4"
MAX. INLET PRESSURE, LP	14"	14"	14"	14"	14"
MIN. INLET PRESSURE, LP	8"	8"	8"	8"	8"
BTU/HR INPUT	399,000	500,000	600,000	725,000	850,000
BTU/HR OUTPUT (HIGH FIRE)	392,000	489,000	585,000	705,000	824,500
BTU/HR OUTPUT (LOW FIRE)	39,200	48,900	83,571	100,714	117,785
ELECTRICAL					
VOLTAGE/HEATER	120	120	120	120	120
VOLTAGE/CONTROL	24	24	24	24	24
TOTAL AMPS (BOILER & PUMPS)	<12	<12	<12	<12	<12
# OF ELECTRICAL CONNECTIONS	1	1	1	1	1
DIMENSIONS					
HEIGHT	55-1/2"	55-1/2"	55-1/2"	56"	56"
WIDTH OF POOL HEX	-	-	-	-	-
WIDTH OF FRAME	29-1/4"	29-1/4"	29-1/4"	29-1/4"	29-1/4"
DEPTH	62-1/2"	62-1/2"	62-1/2"	62-1/2"	62-1/2"
SERVICE CLEARANCES					
FRONT	30"	30"	30"	30"	30"
BACK OF PACKAGE	18"	18"	18"	18"	18"
RIGHT SIDE OF BOILER	0"	0"	0"	0"	0"
LEFT SIDE OF BOILER	0"	0"	0"	0"	0"
TOP	24"	24"	24"	24"	24"
POOL HEAT EXCHANGER (RECOMMEND ALL SIDES)	18"	18"	18"	18"	18"
POOL HEAT EXCHANGER					
RECOMMENDED POOL WATER FLOW (GPM)	52	65	78	94	90
CONNECTION SIZE	2"	2"	2"	2"	2"
DIRECT VENTING					
VENT SIZE	4"	4"	4"	6"	6"
AIR INLET SIZE	4"	4"	4"	4"	4"
VENT CATEGORY	IV	IV	IV	IV	IV
VENT MATERIAL	PVC/CPVC/PP /SS	PVC/CPVC/PP /SS	PVC/CPVC/PP /SS	PVC/CPVC/PP /SS	PVC/CPVC/PP /SS