

	WHP125R	WHP185R SINGLE PASS	MULTI PASS
PERFORMANCE*			
BTUH HEATING	129,000	194,800	
BTUH COOLING	93,515	137,820	
COP HEATING	3.60	3.40	
COP COOLING	2.60	2.40	
COP COMBINED	6.30	5.80	
LBS.R513A	14	23	
COMPRESSOR TYPE	SCROLL	SCROLL	
WATER - MULTIPASS			
SOURCE WATER INLET CONNECTION	1-1/2"	2"	
SOURCE WATER OUTLET CONNECTION	1-1/2"	2"	
SOURCE WATER FLOW RATE (GPM)	23	33	
HEATED WATER INLET CONNECTION	1-1/2"	2"	
HEATED WATER OUTLET CONNECTION	1-1/2"	2"	
HEATED WATER FLOW RATE (GPM)	20	30	
WATER - SINGLE PASS			
SOURCE WATER INLET CONNECTION	1-1/2"	2"	
SOURCE WATER OUTLET CONNECTION	1-1/2"	2"	
SOURCE WATER FLOW RATE (GPM)	23	33	
HEATED WATER INLET CONNECTION	1-1/2"	2"	
HEATED WATER OUTLET CONNECTION	1-1/2"	2"	
HEATED WATER FLOW RATE (GPM)	12	18.0	
ELECTRICAL			
208V-230/3PH/60HZ			
RLA	52	70	74
MCA	64	8	91
MOCP	110	150	160
440V-480V/3PH/60HZ			
RLA	25	33	34
MCA	30	40	42
MOCP	50	70	70
DIMENSIONS			
HEIGHT	40"	40"	
WIDTH	31"	31"	
LENGTH	52"	52"	
SHIPPING WEIGHT (LBS)	649	938	
OPERATING WEIGHT (LBS)	667	970	
SERVICE CLEARANCES (REQUIRED)			
FRONT	36"	36"	
REAR	24"	24"	
RIGHT SIDE	0"	0"	
LEFT SIDE (WATER CONNECTIONS)	24"	24"	
SOUND PRESSURE (dB)**	Front: 63.9 dB, Left: 66.8 dB, Right: 65.9 dB, Rear: 65.7 dB	Front: 67.0 dB, Left: 68.1 dB, Right: 69.3 dB, Rear: 71.1 dB	

*Recovery rate at 80°F source 100% water, DHW 50° EWT, 140°F LWT

**Sound Pressure recorded 3' from unit face, 3' from ground

LEGEND

COP: Coefficient of Performance

SCCR: Short-Circuit Current Rating

RLA: Rated Load Amps

MCA: Maximum Current Ampacity

MOCP: Minimum Overcurrent Protection