

SMART HEAT PUMP HYBRID WATER HEATER

Submittal Sheet

HPSA-Sub-03

## SMART ELECTRIC HEAT PUMP WATER HEATERS


Job Name:	Model No.	Gal. Cap
Location:	Voltage/Phase	kW
Engineer:	Recovery Rate in GPH	@°F Rise
Agent/Wholesaler:	Equipment Tag(s):	
Contractor:		
NOTES:		

## **Standard Features**

- > Heat Pump w/Elements
- > Glass-lined Steel Tank
- Smart Anode
- LED Display
- > Non-CFC Foam Insulation
- > iCOMM<sup>™</sup> Smart Connectivity
- > Leak Protection Technology
- > CSA Certified and ASME Rated Temperature & Pressure Relief Valve
- > Top and Front Water Connections for Easy Installation
- > Brass Drain Valve
- > 10 Year Limited Tank and Parts Warranty\* (See warranty for details)
- \*1 Year Limited Tank and Parts Warranty When Installed in Commercial Applications



## Smart Electric Heat Pump Water Heater w/Leak Protection Technology Dimensions & Specifications



FOR EASE IN ORDERING BY MODEL NUMBER:

HPS A 050 K D SHIRT HEIT PURS LIMM WITHS VOLINEE ANNA ORACITA ELEMENT OF

This heater has a 10 year warranty. It is a Smart Heat Pump model, has a 50 gallon capacity with a 208/240 volt, 4500 watt upper element and 4500 watt lower element.

Model Number	Nominal Gal. Cap.	Rated Gal. Cap.	Input Watts	Standard Voltage	1st Hr. Rating	UEF	A	B	C	D	E	F	Ship Wt
HPSA050KD	50	46	4500	208V/240V	65	3.80	63″	22″	40.5″	3.75″	43.5″	48″	196
HPSA065KD	66	67	4500	208V/240V	82	3.70	61.5″	26.5″	38.25″	4″	41.25″	46″	284
HPSA080KD	80	82	4500	208V/240V	95	3.88	69″	26.5″	46.5″	4″	50.5″	54.5″	302

\* Water connections are 3/4" on an 8" centerline.

\*\* Requires provision for non-acidic condensate draining - if a suitable drain is not available, a condensate pump is required.

\*\*\*Requires 208/2400 VAC 50/60Hz single phase 30 amp power supply.



