

COMMERCIAL ELECTRIC WATER HEATERS

COMPACT ASME HI-POWER ELECTRIC MODELS

5 to 120 Gallon - ASME Construction

STANDARD FEATURES

ADVANCED ELECTRONIC CONTROLS – LCD readout displays operational and diagnostic information in words, not codes. Features Low Water Cutoff, Enable / Disable Contacts, Element Sensing and Night Setback.

GLASS-LINED STEEL TANK – The durable glass lining is fused to the tank at 1600°F to assure lasting protection against rust and corrosion while providing clean, clear hot water. ASME construction – 150 psi working pressure on all models.

POWERED ANODE – Combined magnesium anode and powered anode provide extra protection from corrosion for long trouble-free service.

HEATING ELEMENT – Incoloy sheathed immersion type heats water faster, more economically. Low watt density, (75 watts/in²)

ENERGY CUT-OFF – Shuts off electrical power to the elements should the water temperature in the tank reach 205°F.

ASME TEMPERATURE AND PRESSURE RELIEF VALVE – Factory supplied.

NON-CFC FOAM INSULATION – Superior material formulation provides uniform tank coverage with a thick blanket of insulating foam. This non-CFC polyurethane closed cell foam minimizes standby losses and maximizes heat retention.

HINGED ACCESS DOOR – Provides easy access to electrical controls.

IMMERSION THERMOSTATS WITH CONTACTORS – Thermostat settings range from 80°-180°F and can be adjusted to “off” position.

3 YEAR LIMITED TANK WARRANTY, 1-YEAR LIMITED PARTS WARRANTY
See warranty for details

OPTIONAL EQUIPMENT

ALARM ON ANY FAILURE

TEMPERATURE & PRESSURE GAUGE

4" X 6" HANDHOLE CLEANOUT

ICC CONTROL, BACNET AND MODBUS



Lochinvar®
HIGH EFFICIENCY BOILERS & WATER HEATERS

DIMENSIONS AND SPECIFICATIONS

Model Number	Gallon Capacity	Min kW	Max kW	A	B	C	D	Water Conn.	Shipping Weight
LCA-5(X)kW	5	3	3	22"	16"	24"	4-1/4"	3/4"	82
LCA-10(X)kW	10	3	6	28-1/4"	18"	26"	5-1/4"	3/4"	116
LCA-20(X)kW	20	3	18	31-3/4"	22"	28"	5-3/4"	3/4"	145
LCA-30(X)kW	30	12.3	24	43-1/4"	22"	28"	5-3/4"	3/4"	218
LCA-40(X)kW	40	12.3	36	54-3/4"	22"	28"	5-3/4"	3/4"	245
LCA-50(X)kW	50	12.3	90	66-1/4"	22"	28"	5-3/4"	3/4"	291
LCA-65(X)kW	65	12.3	90	57-1/4"	26-1/2"	32-1/2"	11-1/2"	1-1/4"	344
LCA-80(X)kW	80	12.3	90	58-1/4"	28"	35"	12-1/2"	1-1/4"	406
LCA-100(X)kW	100	12.3	90	70-1/4"	28"	35"	12-1/2"	1-1/4"	419
LCA-120(X)kW	120	12.3	90	70-1/4"	30-1/4"	37"	12-1/2"	1-1/4"	453

NOTE: Allow 24" clearance from front access panel for service and maintenance.

VOLTAGE SCHEDULE

T - 208V / 1 or 3 PH	3 to 24 kW	W - 277V / 1 PH	3 to 45 kW
J - 208V / 1 PH	30 to 45 kW	V - 480V / 1 PH	3 to 90 kW
K - 208V / 3 PH	30 to 90 kW	X - 480V / 3 PH	3 to 90 kW
P - 240V / 1 or 3 PH	3 to 54 kW	Y - 380V / 3 PH	3 to 90 kW
A - 240V / 1 PH	60 kW	Z - 415V / 3 PH	3 to 90 kW
B - 240V / 3 PH	60 to 90 kW	M - 575V / 3 PH	3 to 90 kW
		N - 600V / 3 PH	3 to 90 kW



AMPERAGE TABLE

kW	SINGLE PHASE			THREE PHASE			
	208V	240V	277V	480V	208V	240V	480V
3	14.4	12.5	10.8	6.3	8.3	7.2	3.6
6	28.8	25.0	21.7	12.5	16.7	14.4	7.2
9	43.3	37.5	32.5	18.8	25.0	21.7	10.8
12	57.7	50.0	43.3	25.0	33.3	28.9	14.4
15	72.1	62.5	54.2	31.3	41.6	36.1	18.0
18	86.5	75.0	65.0	37.5	50.0	43.3	21.7
24	115.4	100.0	86.6	50.0	66.6	57.7	28.9
30	144.2	125.0	108.3	62.5	83.3	72.2	36.1
36	173.1	150.0	130.0	75.0	99.9	86.6	43.3
45	216.3	187.5	162.5	93.8	124.9	108.3	54.1
54	N/A	225.0	194.9	112.5	149.9	129.9	65.0
60	N/A	250.0	216.6	125.0	166.5	144.3	72.2
75	N/A	N/A	N/A	156.3	208.2	180.4	90.2
90	N/A	N/A	N/A	187.5	249.8	216.5	108.3

Note: All ASME models with an amp draw in excess of 120 amps receive factory installed internal fusing.

BY MODEL NUMBER					
L	C	A	40	X	36
LOCHINVAR	COMPACT	ASME	GALLON CAPACITY	VOLTAGE	KILOWATTS

This heater is a Compact Hi-Power, 480 volt, 3 phase, 36 kW, 40 gallon water heater with ASME construction.



Note: Outlet connection for 5 thru 50 models 3/4" NPT.
Outlet connection for 65 thru 120 models 1-1/4" NPT.


For technical information call 800-722-2101. Lochinvar, LLC reserves the right to make product changes or improvements without prior notice.

GPH RECOVERY RATE

INPUT		Recovery Rate (GPH @ °F Rise)											
kW	Btu/hr	30°F	40°F	50°F	60°F	70°F	80°F	90°F	100°F	110°F	120°F	130°F	140°F
3	10,239	41	31	34	20	17	15	13	12	11	10	10	9
6	20,478	82	62	49	41	35	31	27	25	22	21	19	18
9	30,717	123	92	74	62	53	46	41	37	34	31	28	26
12	40,956	164	123	98	82	70	61	55	49	45	41	38	35
15	51,195	205	154	123	102	88	77	68	61	56	51	47	44
18	61,434	246	184	148	123	105	92	82	74	67	62	57	53
24	81,912	328	246	197	164	140	123	109	98	90	82	76	70
30	102,390	410	308	246	205	176	154	137	123	112	103	95	88
36	122,868	492	369	295	246	211	184	164	148	134	123	113	105
45	153,585	615	461	369	307	263	230	205	184	168	154	142	132
54	184,302	738	554	443	359	316	277	246	221	201	185	170	158
60	204,780	819	615	492	410	351	307	273	246	223	205	189	176
75	255,975	1,025	768	615	512	439	384	341	307	279	256	236	219
90	307,710	1,229	922	738	615	527	461	410	369	335	307	284	263



Lochinvar, LLC
300 Maddox Simpson Parkway
Lebanon, Tennessee 37090
P: 615.889.8900 / F: 615.547.1000



LOW LEAD CONTENT

HIV

HPC-05 (Replaces HPC-04 8/18)

(Website Update 7/24) ASB-1K-5/19-Printed in U.S.A.