

EPIC™ FLOOR COMBI PRODUCT SUMMARY
(EFC) 110,000-199,999 BTU/HR

	EFC110	EFC150	EFC199
BOILER			
GALLON CAPACITY	1.8	2.4	3.1
HEATING SURFACE (SQ. FT.)	7.33	11.40	15.02
WATER CONNECTIONS	1"	1"	1"
MAX. WORKING PRESSURE (PSI)	50	50	50
# OF RELIEF VALVES	1	1	1
RELIEF VALVE SIZE	3/4"	3/4"	3/4"
RELIEF VALVE RATING (MBH)	535	535	535
RELIEF VALVE PRESSURE RATING (PSI)	50	50	50
DOMESTIC WATER			
WATER CONNECTIONS	3/4"	3/4"	3/4"
77°F ΔT DHW DELIVERY @ (GPM)	2.6	3.6	4.8
MAX. WORKING PRESSURE (PSI)	150	150	150
GAS			
INLET CONNECTION	1/2"	1/2"	1/2"
MAX. INLET PRESSURE, NAT	14.0" w.c.	14.0" w.c.	14.0" w.c.
MIN. INLET PRESSURE, NAT	4.0" w.c.	4.0" w.c.	4.0" w.c.
MAX. INLET PRESSURE, LP	14.0" w.c.	14.0" w.c.	14.0" w.c.
MIN. INLET PRESSURE, LP	8.0" w.c.	8.0" w.c.	8.0" w.c.
BTU/HR INPUT	110,000	150,000	199,999
BTU/HR OUTPUT (HIGH FIRE)	104,500	142,500	189,050
BTU/HR OUTPUT (LOW FIRE)	10,450	14,250	18,905
ELECTRICAL			
VOLTAGE/HEATER	120	120	120
VOLTAGE/CONTROL	24	24	24
TOTAL AMPS	2.2	2.2	2.2
# OF ELECTRICAL CONNECTIONS	1	1	1
DIMENSIONS			
HEIGHT	47.5"	47.75"	47.75"
WIDTH	19.25"	21"	21"
DEPTH	21"	21.25"	21.25"
SERVICE CLEARANCES			
FRONT	24"	24"	24"
RIGHT SIDE	12"	12"	12"
LEFT SIDE	12"	12"	12"
BACK	6"	6"	6"
TOP	12"	12"	12"
DIRECT VENTING			
SIZE	3"	3"	3"
VENT CATEGORY	IV	IV	IV
VENT MATERIAL	PVC/CPVC/SS/PP	PVC/CPVC/SS/PP	PVC/CPVC/SS/PP