



POWER-FIN® WATER HEATER PRODUCT SUMMARY

(PF) 500,000 - 2,000,000 BTU/HR (5:1 Turndown)

PF-0502 (M9) PF-0752 (M9) PF-1002 (M9) PF-1302 (M9) PF-1501 (M9) PF-1701 (M9) PF-2001 (M9)

WATER							
GALLON CAPACITY	3.5	4.0	4.5	5.0	5.5	5.8	6.0
HEATING SURFACE (SQ. FT.)	58.7	88.2	116.0	149.2	156.8	177.8	209.4
WATER CONNECTIONS	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"
DRAIN	2 @ 3/4"	2 @ 3/4"	2 @ 3/4"	2 @ 3/4"	2 @ 3/4"	2 @ 3/4"	2 @ 3/4"
MAX. WATER FLOW RATE (GPM)	75	75	75	75	90	90	90
HEAD LOSS (FT. OF HD.)	7.2	7.5	7.8	9.5	10.5	11.8	12.4
MAX. WORKING PRESSURE	160	160	160	160	160	160	160
MAX. WATER HARDNESS (GPG)	25	25	25	25	25	25	25
GPH @ 70°F RISE	748	1,122	1,496	1,961	2,260	2,561	3,013
GPH @ 100°F RISE	527	791	1,054	1,371	1,582	1,793	2,109
GPH @ 140°F RISE	380	570	760	1,005	1,130	1,281	1,506
# OF RELIEF VALVES	1	1	1	1	1	1	1
RELIEF VALVE SIZE	3/4"	3/4"	3/4"	3/4"	1"	1"	1"
RELIEF VALVE RATING (MBH)	1,912	1,912	1,912	1,912	2,155	2,155	2,155
RELIEF VALVE PRESSURE RATING (PSI)	150	150	150	150	150	150	150
RELIEF VALVE TEMPERATURE (°F)	210	210	210	210	210	210	210
GAS							
INLET CONNECTION	1"	1-1/4"	1-1/4"	1-1/4"	1-1/2"	1-1/2"	1-1/2"
MAX. INLET PRESSURE, NATURAL GAS	10.5" w.c.	10.5" w.c.	10.5" w.c.	10.5" w.c.	14.0" w.c.	14.0" w.c.	14.0" w.c.
MIN. INLET PRESSURE, NATURAL GAS	3.2" w.c.	3.2" w.c.	3.2" w.c.	3.2" w.c.	4.0" w.c.	4.0" w.c.	4.0" w.c.
MANIFOLD PRESSURE, NATURAL GAS	-8.3" w.c.	-4.6" w.c.	-7.1" w.c.	-6.8" w.c.	-4.1" w.c.	-5.1" w.c.	-4.0" w.c.
MAX. INLET PRESSURE, LP GAS	13.0" w.c.	13.0" w.c.	13.0" w.c.	13.0" w.c.	14.0" w.c.	14.0" w.c.	14.0" w.c.
MIN. INLET PRESSURE, LP GAS	11.0" w.c.	11.0" w.c.	11.0" w.c.	11.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.
MANIFOLD PRESSURE, LP GAS	-9.7" w.c.	-5.5" w.c.	-9.3" w.c.	-9.5" w.c.	-2.3" w.c.	-2.6" w.c.	-2.4" w.c.
BTU/HR INPUT	500,000	750,000	1,000,000	1,300,000	1,500,000	1,700,000	2,000,000
ELECTRICAL							
VOLTAGE/HEATER	120	120	120	120	120	120	120
VOLTAGE/PUMP	120	120	120	120	120	120	120
VOLTAGE/CONTROL	24	24	24	24	24	24	24
TOTAL AMPS W/PUMP	12.4	12.4	12.4	12.4	17.1	17.1	17.1
# OF ELECTRICAL CONNECTIONS	1	1	1	1	1	1	1
DIMENSIONS							
HEIGHT	44-1/2"	52-1/4"	59-1/4"	67-3/4"	65-1/2"	70"	76-3/4"
WIDTH	23-1/4"	23-1/4"	23-1/4"	23-1/4"	27-1/4"	27-1/4"	27-1/4"
DEPTH (INCLUDES PUMP)	42-3/4"	42-3/4"	42-3/4"	42-3/4"	56"	56"	56"
SERVICE CLEARANCES							
FRONT	24"	24"	24"	24"	24"	24"	24"
BACK (PIPING)	24"	24"	24"	24"	24"	24"	24"
RIGHT SIDE	0"	0"	0"	0"	0"	0"	0"
LEFT SIDE	0"	0"	0"	0"	0"	0"	0"
TOP	24"	24"	24"	24"	24"	24"	24"
VENTING							
SIZE	7" / 4"	9" / 5"	10" / 6"	12" / 8"	8" / 6"	9" / 7"	10" / 8"
VENT CATEGORY	II / IV	II / IV	II / IV	II / IV	II / IV	II / IV	II / IV
VENT MATERIAL	AL29-4C	AL29-4C	AL29-4C	AL29-4C	AL29-4C	AL29-4C	AL29-4C

Lochinvar Corporation • 300 Maddox Simpson Pkwy • Lebanon, TN 37090 • 615-889-8900 / Fax: 615-547-1000

www.Lochinvar.com